


R5-24G-TYZ/S1 (ADJ)

The CTL-SEN-R5/2117 is a high-precision human presence sensor powered by advanced 24GHz FMCW millimeter-wave radar technology. Featuring a versatile 0 to 60° adjustable detection angle, it allows for flexible positioning to target specific areas and minimize blind spots. By detecting micro-motions (such as breathing), the sensor accurately identifies both moving and stationary occupants. With a detection range of up to 8.0 meters and an integrated high-precision illuminance sensor (0 to 32,000 Lux), it is engineered to deliver optimal energy efficiency and automation for smart homes, commercial offices, and healthcare facilities.



Interface



- 1. Multifunction Window (LED / Illuminance Sensor / IR)
- 2. Radar Sensing Surface (0 to 60° adjustable)
- 3. Power Input (AC 100 to 240 V)
- 4. Spring Clip
- 5. Pairing Button


Features

- Supports motion, micro-motion, and stationary presence detection.
- Integrated high-precision sensor for accurate indoor illuminance monitoring.
- Features 1 relay output
- Features a 0 to 60° adjustable detection angle for precise zone targeting.
- Sensitivity and detection range can be configured independently.
- Supports parameter configuration and query via IR remote control.
- Indicator LED brightness automatically adjusts to ambient light levels.


Specifications

Communication Type	Tuya-ZigBee
Input Voltage	AC 100 to 240 V
Power Consumption	0.5 W (Max)
Relay Output	Normally Open Mode, Normally Closed Mode
Relay Load	AC 100 to 240 V, ≤ 2 A
Indicator Light	LED
Detection Mode	24GHz FMCW Radar
Operating Frequency	24.00 to 24.25 GHz
Transmit Power	≤ 10 dBm
Installation Method	Recessed Ceiling Mount
Mounting Height	2.0 to 4.0 m
Detection Angle	360°
Detection Coverage	Mounting Height: 3 m At 0°: Φ 2.0 m detection range At 30°: 5.0 × 3.6 m detection range At 60°: 8.0 × 8.0 m detection range
Detection Range	1.5 to 8.0 m (sensor to target)
Sensitivity	0% to 100%
Illuminance Monitoring	0 to 32,000 Lux (Accuracy ±4%)
Delay Time	1 to 3,600 seconds
Product Size	Φ65 mm × 60 mm
Cutout Size	Φ55 mm
Product Weight	82.5 g
Cable Specification	UL1015 18AWG
Operating Environment	Indoor -20 to 45°C, Humidity < 95% RH (Non-condensing)
Storage Temperature	-40 to 85°C
Protection Level	IP20
Housing Material	PC


Detection Range



Wiring Diagram



Dimensions



Installation Notes

Interference Avoidance: Avoid installing near constantly moving objects (e.g., curtains, plants) or large reflective surfaces (e.g., metal ducts, mirrors) to prevent false triggering.

Device Spacing: Maintain a minimum distance of 4 meters between multiple sensors to prevent mutual interference.

Mounting: Ensure the installation surface is vibration-free. Note that radar signals can penetrate surfaces; avoid moving objects directly behind the installation wall/ceiling.

Wiring Safety: Disconnect power before wiring. Use certified cables and ensure the circuit includes appropriate short-circuit and overload protection.

Disclaimer: Specifications are subject to change without notice. Please follow all wiring diagrams strictly. The manufacturer is not liable for issues caused by improper installation.

Available Accessories



Remote Control (60.99.00C1)

Ordering Information

P/N	Short Name	Model	Remarks
60.50.2117	R5-24G-TYZ/S1 (ADJ)	CTL-SEN-R5/2117	Main Unit
60.99.00C1	RC1	RC1	Accessory